

**ENGINE BASED KINETIC ENERGY RECOVERY SYSTEM FOR VEHICLES**

## 1. Technical Field

**[0001]** The invention relates to vehicles with internal combustion engines and more particularly, to a kinetic energy recovery system for such vehicles.

## 2. Description of the Problem:

**[0002]** Most motor vehicles equipped with internal combustion engines dissipate kinetic energy during stopping through use of friction brakes and engine compression braking, rather than capturing and storing the energy for reuse. It is widely recognized that this arrangement is highly wasteful of energy and that recapture of the energy for use in moving the vehicle from standing starts is desirable. However, prior attempts to provide for recapture of the energy for reuse, as represented by hybrid gasoline/electric vehicles, have been difficult to justify economically at low energy prices. These vehicles use both an internal combustion engine and electric motors to move the vehicle. During braking the motors operate as generators to retard the vehicle and convert the vehicle's kinetic energy to electricity which is stored in batteries. This power can then be used to power the motors and move the vehicle. Such vehicles are highly efficient. However, they are also very complex and as a result cost substantially more to design and build than conventional vehicles. They also have high maintenance costs associated with periodically replacing the battery plant.

**[0003]** An effective energy recovery system for a vehicle using an internal combustion engine must provide for the efficient storage of the recaptured energy. Alternatives to battery storage include fly wheels and compressed air. Implementation of systems based on these alternative modes of energy storage have been hobbled by the limitations of the recapture and utilization mechanisms.

**[0004]** Considering compressed air systems in particular, designers have typically looked to clutching the wheels to air pumps to provide vehicle speed retardation and a source of high pressure air. This has been done notwithstanding the fact that the engine itself is a pump, is connected to some of the wheels by the vehicle's drive line and can be used for engine compression braking. Unfortunately, even diesel engines, when operated as pumps, operate at too low of a pressure to provide an efficient and compact kinetic energy capture and utilization system.

**[0005]** Engine compression braking is implemented by operating an internal combustion engine as an air compressor and then dissipating the energy stored compressing the air through the vehicle's exhaust. In order to run a diesel as a compressor, fuel flow is cut off to one or more the engine's cylinders. The vehicle's momentum is coupled back to the engine crankshaft by the vehicle drive train causing the pistons in the non-firing cylinders to continue to cycle. The cylinders' intake valves operate to allow air to be drawn for compression strokes, but the cylinders' exhaust valves are opened at or just before top dead center (TDC) of the pistons' compression cycles to exhaust the air, releasing the energy potential of the compressed gas air. The energy is dissipated in friction upon release to the open atmosphere. Internal combustion engines can dissipate vehicle kinetic energy at a rate close to the engine's rated power.

**[0006]** Internal combustion engines operate as relatively low compression pumps. A diesel may generate approximately a 25 to 1 compression ration, meaning that air drawn into the cylinder at close to ambient pressure is compressed to no greater than about 375 psi. In practice only about 300 psi is achieved due to a partial vacuum in the intake manifold and frictional losses. Absent some modification of a cylinder to operate as a higher compression pump, which complicates the engine and may compromise its performance, the compressed air must be recovered from the exhaust manifold, which entails storage at a still lower pressure.

**[0007]** Assuming that air of sufficient pressure can be made available to propel the vehicle on taking off from a standing start, a question has also remained of how,

and when, to make use of the compressed air. Also of interest is when and how to run the engine for air compression to optimize vehicle operation and reduce pollution. What is needed is a way of boosting pump operation of an internal combustion engine on a vehicle to sufficiently high pressures to be used for moving the vehicle, all while minimizing changes to the vehicles drive train and engine to produce a system both economical and reliable.

### **SUMMARY OF THE INVENTION**

**[0008]** One object of the invention is to improve the efficiency of motor vehicles equipped with internal combustion engines.

**[0009]** Another object of the invention is to provide recovery of kinetic energy of a vehicle during driver or speed control system initiated vehicle speed retardation.

**[0010]** Still another object of the invention is efficiently to utilize compressed air to provide supplemental torque for an internal combustion engine.

**[0011]** Yet another object of the invention is to combine vehicle operational data to identify efficient opportunities for capture of kinetic energy for storage and reuse for vehicle speed boosting.

**[0012]** The invention provides for these and other objects by providing a vehicle with a multi-cylinder diesel engine which can be operated in a split mode with one or more cylinders diverted to operation as air compressor stages or adapted for use for engine compression braking. Valves are incorporated into the exhaust pipes for selected cylinders which may be closed to prevent or delay exhaust venting from the exhaust pipes. Fluid amplifiers communicate with these exhaust pipes to operate as second stage high compression pumps. Compressed air from the second stage compressors is delivered to a high pressure storage tank for later use to meet high transient torque demand. In the preferred embodiment, high pressure air is used to drive a hydraulic motor coupled to an automatic or semi-automatic transmission and

thereby displace torque demands on the engine, especially at takeoff from a standing start. Alternatively, the air may be delivered to an exhaust turbine in a turbo-compounding arrangement to provide additional torque to the engine output shaft. Air may also be forced into the intake manifold of the engines for take offs from a standing start by released compressed air to the drive turbine of a turbo-supercharger.

**[0013]** Additional effects, features and advantages will be apparent in the written description that follows.

### **BRIEF DESCRIPTION OF THE DRAWINGS**

**[0014]** The novel features believed characteristic of the invention are set forth in the appended claims. The invention itself however, as well as a preferred mode of use, further objects and advantages thereof, will best be understood by reference to the following detailed description of an illustrative embodiment when read in conjunction with the accompanying drawings, wherein:

**[0015]** **Fig. 1** is a perspective view of a truck tractor with which the invention is advantageously employed.

**[0016]** **Fig. 2** is a schematic diagram showing an exhaust gas retention and two stage compression system.

**[0017]** **Figs. 3A-D** are schematics illustrating operation of a two stage high pressure air compression system using an engine cylinder as a first, low pressure stage of the pump.

**[0018]** **Fig. 4** is a schematic of an kinetic energy recovery and recycling system using a hydrostatic motor to provide supplemental torque to a transmission.

**[0019]** Fig. 5 is a schematic of a kinetic energy recovery and recycling system for a turbo-compounded engine.

**[0020]** Fig. 6 is a schematic of a kinetic energy recovery and recycling system for a turbo-supercharged engine.

**[0021]** Fig. 7 is a simplified flow chart illustrating operation of the invention.

### **DETAILED DESCRIPTION OF THE INVENTION**

**[0022]** Fig. 1 illustrates in a perspective view a truck tractor 10 comprising a cab 11 mounted on a chassis 12. A plurality of wheels 13 depend from the chassis. Tractor 10 includes conventional major systems for a vehicle, including a drive train having a diesel engine and a transmission. Tractor 10 also includes air powered drive train boosters as described below. The invention is preferably applied to medium and large trucks which have compressed air systems for brake operation or for starting. These vehicles are typically equipped with a multi-cylinder diesel, which is often adapted for engine compression braking, and compressed air tanks. It will be understood that while the invention is preferably applied to diesels, it would also work, with modification, on internal combustion engines using spark initiated combustion. It may also be advantageously applied to delivery trucks and other vehicles used heavily for stop and go driving.

**[0023]** Referring now to Fig. 2 an engine air compression and diversion system 18 is illustrated. Compression system 18 uses one or more of the cylinders 32 of a bank 24 of cylinders of a multi-cylinder diesel engine as first stage pumps. In normal operation a piston 102 moves in a conventional, reciprocating fashion within a cylinder 32 with the result that space 104 between the piston and valves 106 and 110 varies in volume. A diesel is conventionally operated as a four cycle engine. Initially intake valve 106 and exhaust valve 110 may be assumed closed. The first cycle is initiated with piston 102 at the top of its travel in cylinder 32 (referred to conventionally as top dead center ("TDC")). Intake valve 106 is opened and air is

drawn into cylinder **32** with the following downstroke of piston **102** through the opened intake valve **106** from an intake manifold **108**. Intake valve **106** is closed when piston **102** reaches the bottom of its travel in the piston and the air is compressed by the subsequent upward movement of piston **102**. This compression stroke of piston **102** develops an approximately 25 to 1 compression ratio of air in the cylinder, raising the temperature of the air above the ignition point of the fuel. Compression ignition of the fuel results upon fuel being injected into cylinder **32** as the piston approaches TDC. The burning air fuel mixture substantially raises pressure in cylinder **32** substantially increasing the downward force on piston **102**. This produces a downward power stroke of piston **104**. An upward exhaust stroke of piston **102** follows for which exhaust valve **110** is opened. During the exhaust stroke the combustion byproduct is exhausted through exhaust valve **110** into a cylinder exhaust chamber **112**. Exhaust chamber **112** can pass air or combustion byproducts from cylinder **32** to an exhaust manifold **17**, which collects exhaust gas from bank **24** of cylinders, or retain the air for use of the fluidic amplifier **83**. Exhaust valve **110** closes as piston **102** finishes the exhaust stroke. The four cycles repeat as long as the cylinder is firing.

**[0024]** Contemporary practice provides for computer based control of many vehicle and engine functions, usually organized by systems. An engine controller **20** is representative of such a computer used to monitor and control the operation of diesel **16**. Engine controller **20** times fuel injection to each cylinder **32** by control of a fuel injection controller **48**. A camshaft rotates in synchronous with a crank shaft, which in turn is coupled to the pistons in cylinders **32**. Thus camshaft position is related to the phase of each piston relative to TDC. Fuel injection is timed in relation to the cam phase position, provided by a cam phase (engine position) sensor **42**. Fuel injection is handled by an injector controller **48**. The timing of closing and opening of the intake valve **106** and an exhaust valve **110** are effected by engine controller **20** through valve actuators **124** and **126**, respectively. Engine controller **20** is also used to operate a starter **50**, which may be an air starter using compressed air from a compressed air tank **70**. Where an air starter, or some other device using compressed air at the request of engine control module **20** is used, the engine

control module is connected to control a solenoid **87** for positioning a valve **85**. Air valve **85** connects compressed air tank **70** to the device, here an air starter **50**, or as described hereinafter, a torque output booster. The pistons of an engine are connected to a rotatable crankshaft (not shown) which is in turn connected to an output shaft and transmission which continue to move the pistons absent fuel flow to the cylinders, as long as the vehicle retains momentum.

**[0025]** The intake and exhaust valves **106**, **110** may be hydraulically actuated using pressurized engine oil, with the camshaft used to operate hydraulic valves controlling intake and exhaust valve operation. Hydraulic valve control may then be overridden by engine controller **20** through valve controllers **124** and **126**. For future camless engines, crankshaft phase position may be substituted for cam phase position to the same effect in coordinating the injection of fuel with piston phase and valve timing. In a camless engine, hydraulic valve control uses pressurized engine oil and remains under the control of valve controllers **124** and **126**. The position of an exhaust collection shutter valve **34** is coordinated by engine controller **20** using a solenoid **35** as described below.

**[0026]** Engine operation as an air pump requires coordination of the operation of fuel injectors, intake valves, exhaust valves and the exhaust diversion valves. Engine cylinders are operated as pumps in split mode operation, or during engine compression braking. Pump operation entails fuel flow cut off to one or more cylinders **32**. Cylinder **32** operates as an air pump when at least some of the remaining cylinders of the engine continue to fire to keep the engine turning over, or when vehicle momentum is coupled to the engine crankshaft from the transmission. After fuel is cut off to a pumping cylinder, the cam actuated lifters can continue to operate intake and exhaust valves **106** and **110**, however, for more efficient engine compression braking, the intake valve is open during every down stroke and the exhaust valve is briefly opened as the piston **102** approaches TDC with every up stroke.

**[0027]** Under conditions where some engine power is required, but air pressure status indicates a need for air, valve operation may be altered, and still allow operation of the high pressure air compression system **18**. It is not usually necessary under these conditions to draw air to a pumping cylinder **32** and it is preferable not to draw air away from the firing cylinders, or to impose as large a load on the engine as would occur if the non-firing cylinder of the engine were operating, in effect, as a compression brake. For a preferred embodiment of a fluidic amplifier **83**, the intake valve **106** may be left closed and the exhaust valve **110** left open after an initial air charge is drawn into cylinder **32** and the fluidic amplifier **83** will continue to supply high pressure air, at least as long as the charge does not leak away. To compensate for such leakage the charge in the pumping cylinder **32** may be occasionally refreshed by opening intake valve **106** during a cycle.

**[0028]** Cylinder **32** operates as the first, or low pressure stage, of a two stage pump. Compressed air from cylinder **32** is used to drive a second or high pressure stage pump. In order to avoid modification of the cylinder **32**, some modification of the exhaust manifold **17**, or to the exhaust chamber **112** from an individual cylinder, is required to divert the air to drive the high pressure pumps. Shutter valve **34** is located in the wall of exhaust chamber **112** and connects the chamber with exhaust manifold **17**. A fluidic amplifier **83**, which provides the high pressure stage, communicates with the exhaust chamber **112**. Modification of the exhaust system for one cylinder **32** to accommodate one shutter valve **34** and fluidic amplifier **83** is illustrated, but it will be understood that an exhaust system can be modified allowing more than one of cylinders **32** to operate as first stage air pumps. It will also be understood that cylinders may have more than one intake or exhaust valve and that illustration of and reference to the cylinders as having a single valve for exhaust and a single valve for intake has been done for the sake of simplicity in illustration only.

**[0029]** Retention of air pumped from cylinder **32** is controlled by opening and closing shutter valve **34**. A control solenoid **40**, under the control of engine controller **20**, positions valve **34**. When valve **34** is closed, and fuel cut off from cylinder **32**, air is pumped from cylinder **32** during an up stroke into fluidic or pneumatic amplifier **83**.



Pneumatic amplifier draws air from the environment through an intake **183**, compresses the air and exhausts the compressed air through a check valve **120** into a high pressure air tank **70**. Fluid amplifier **83** should have a pressure gain of about 20 to 1 and thus be able to deliver air to compressed air tank at pressures in excess of 2000 psi or twenty times the expected pressure of air from cylinder **32**. Shutter valve **34** also operates to release air from the input side of pneumatic amplifier **83** upon opening, which can occur after a brief delay or during engine compression braking or only after pumping is discontinued, as may be preferred for split mode operation. Fluid amplifier **83** could in theory be run from combustion by product exhaust gas from cylinder **32** at substantially higher pressures, however, such an arrangement would substantially increase back pressure from the exhaust system and thereby reduce the efficiency of the engine. The 2000 psi pressure level is chosen as the contemporary practical economic limit for a motor vehicle compressed air storage system. A higher pressure could be used given progress in seals and tank strength at affordable prices for a mass produced vehicle.

**[0030]** Air compression occurs in response to a need for compressed air and availability of engine power to provide energy for pumping. A need for air is indicated by a downward variance from the maximum pressure limit for air tank **70**. To provide air tank **70** pressure readings, a pressure sensor **91** is provided in fluid communication with air tank **70**. Pressure sensor **91** reports air pressure in tank **70** to a computer, preferably body controller **30**, or to engine control module **20**, depending upon the particular control arrangements provided on a given vehicle. When air pressure in air tank **70** is below the maximum allowed a request for operating air compression system **18** is issued by body controller **30**. The degree to which the air pressure falls below the maximum allowed may also be used as an indication of the priority of the request. In order to avoid frequent cycling of the system on and off, air pressure in tank **70** may be required to fall a certain minimum amount below the maximum limit before air compression system **18** is engaged. A number of control regimens may be implemented and which regimen is used at a given time may depend upon the pressure level short fall. Described here are the mechanisms useful in implementing the regimens. The regimens are executed by

body controller **30**. This computer may also be referred to in the art as a chassis controller or system controller. The functions are implemented on International Truck & Engine vehicles by an electrical system controller.

**[0031]** Finding the preferred periods for operation of the air compression system **18** also requires determining engine load or some other related factor indicative of spare engine capacity. If engine load is low, or better still negative, air compression system **18** can be run at little penalty, and more usually allows energy to be recaptured. Periods of engine compression braking are an ideal opportunity for air compression system **18** operation. Body controller **30** estimates engine load from engine speed, derived from the output of the engine (or cam phase) position sensor **42** and the fuel flow output which are passed to it from engine control module **20**. Body controller **30** also receives inputs, either directly or from other system controllers, which indicate the status or condition of an accelerator pedal/torque request input **54**, a starter button **56**, an ignition switch **58**, a brake pedal position switch **58** and a vehicle speed indication source **59**, all of which may be used to determine other opportunities to initiate air pumping or the need to use air. Under cruising conditions where air tank **70** is fully pressurized, and no demands for air power occur, body controller **30** may determine leakage rates for air tank **70** from periodic sampling of readings from pressure sensor **91**.

**[0032]** A preferred embodiment of the invention will now be described with reference particularly to **Figs. 3A-D** where a schematic of the pneumatic amplifier **83** and shutter valve **34** are illustrated. Pneumatic amplifier **83** comprises an exhaust chamber **112** which functions as a pneumatic amplifier input chamber. Exhaust chamber **112** is exposed to a working surface **308** of a shuttle piston **304**. Shuttle piston **304** is positioned between chamber **112** and pumping chamber **320**. Shuttle piston **304** is mounted to reciprocate in the directions indicated by the double headed arrow "C" allowing air in a pumping chamber **320** to be compressed. A working surface **310** of piston **312** is exposed to pumping chamber **320**. Working surface **308** has approximately 20 times the exposed surface area of working surface **310** meaning that the pressure in pumping chamber **320** balances the pressure in

chamber **302** when it is about 20 times as great, less the rebound force generated by a compression spring **312**. Spring **312** is disposed to urge shuttle piston **304** in the direction "D" up to a limit of the shuttle piston's travel. An intake **183** is provided to the pumping chamber **320**, which admits air to the chamber through a one way check valve **314**. The air drawn into the chamber is preferably dried ambient air. The spring constant of compression spring **312** is selected to substantially prevent movement of shuttle piston **304** during the relatively low transient pressures occurring during the exhaust of combustion gases.

**[0033]** Shutter valve **34** is located in the wall of exhaust chamber **112** and is positioned to control pressurization of the chamber and operation of fluidic amplifier **83**. Exhaust chamber **112** should be made as small as practical to minimize the pressure drop occurring in gas exhausted from cylinder **32** when shutter valve **34** is closed. As illustrated in **Fig. 3A**, valve **34** is in its opened position, allowing combustion by-products to escape from cylinder **32**. With valves **32** and **34** open, reciprocating piston **102** can force exhaust gas from cylinder **32** through the opened exhaust valve **110** as indicated by arrow "A" into cylinder exhaust chamber **112** and out of exhaust chamber **112** through valve **34** as indicated by the arrow "B" to an exhaust manifold **17**.

**[0034]** In **Fig. 3B** pumping of compressed air into compressed air tank **70** is illustrated. Following cessation of fuel injection to cylinder **32** and having drawn a charge of air into cylinder **32**, concurrent with compression stroke of piston **102**, exhaust valve **110** opens to allow air to be forced from cylinder **32** indicated by arrow "A". Shutter valve **34** closes access to exhaust manifold **17** preventing the flow of air into the exhaust manifold. As pressure in exhaust chamber **112** increases, the resistance of spring **312** is overcome and shuttle piston **304** is forced in the direction indicated by the arrow "E", compressing the air in pumping chamber **320** until check valve **120** admits (in the direction indicated by arrow "G") the air to compressed air tank **70**. Again the gain provided by the difference in exposed surface areas of the two ends of the pistons results in a gain of about 20 to 1 in pressurization. The relative areas may be varied to obtain almost any desired gain though. The relative

volumes of the exhaust chamber **302** and the pumping chamber **320** and the travel of shuttle piston **304** are chosen so that shuttle piston **304** does not bottom against spring **312** before pressure in the chamber **320** increases sufficiently to balance the pressure in input chamber **302**.

**[0035]** In **Fig. 3C** a pumping stroke of shuttle piston **304** has completed. Fluid amplifier **83** may be operated without drawing fresh air with each cycle into cylinder **32**. Once a charge of air is drawn into cylinder **32**, valves **106** and **34** are kept closed, and valve **110** left open. For subsequent pumping steps, as piston **104** moves downwardly, air is drawn from chamber **112** through exhaust valve **110** back into cylinder **32**, pulling shuttle piston **304** back into chamber **302**, and thereby drawing air in pumping chamber **320** by a now open check valve **314** as indicated by the arrow "I". Piston **102** reciprocates in cylinder **32** resulting in the same charge of air being forced in and out of exhaust chamber **112**. Using this operational sequence it may be possible to eliminate compression spring **312**, simplifying pneumatic amplifier **83**. The effectiveness of such an arrangement will depend upon the quality of the seal formed by valve **34** and some leakage from exhaust chamber **112** is to be expected. Pumping in this manner may require pressure monitoring in chamber **112** and occasionally opening intake valve **106** may be done to replenish the charge. A pressurized first stage system might be employed where, rather than drawing a fresh air charge, pumping begins with a charge of combustion by product from cylinder **32**. Again the intake valve **106** and shutter valve **34** remain closed and valve **110** would remain open while piston **102** reciprocates. Pumping with valve **106** held closed and valve **110** held open is preferably employed when the engine is under a positive load and it is undesirable that pumping mimic a compression brake or draw air from the intake manifold and thus divert it from the firing cylinders.

**[0036]** **Fig. 3D** reflects the configuration of pumping system **18** for recharging fluidic amplifier **83** or for an intake stroke when the engine is being used for compression braking. Exhaust valve **110** to cylinder **32** has closed and intake valve **106** has opened as piston **102** begins an intake stroke, drawing air from intake manifold **108** into chamber **104**. Shutter valve **34** opens allowing air in exhaust

chamber **112** and exhaust pipe **118** to escape to the exhaust manifold **17**. This results in a pressure drop in chamber **112** which allows a combination of air pressure in pumping chamber **320** and spring **312** to return shuttle piston **304** in the direction indicated by the letter "F" to a neutral position. With movement of the shuttle piston **304**, air pressure drops below ambient pressure in pumping chamber **320** and air is drawn through intake **183** and check valve **314** into the pumping chamber.

**[0037]** Referring now to **Figs. 4, 5 and 6**, the preferred embodiments of the invention are illustrated. Diesel engine **16** is a simplified representation of the engine described above in connection with **Fig. 2**. The invention is employed to best effect when the various vehicle systems are monitored and data related to operating variables are exchanged between system control processes. This arrangement allows determination of advantageous times to compress air and further determines when there is a demand for air and the capacity to provide it. Compressed air may be applied to vehicle systems such as an air brake system **95** used by a trailer or by an air starter **50** used for starting a diesel engine. Compressed air at the high pressures efficiently recovered by the two stage air compression system described here can also be employed to provide supplemental torque on demand. Utilization of the air also depends upon vehicle operating conditions. In contemporary vehicles major vehicle systems, e.g. the drive train, the engine, the brake system, and so on, are increasingly under the control of system controllers. The system controllers, including an engine controller **20**, a transmission controller **130**, an anti-lock brake system (ABS) controller **99**, a gauge controller **14**, and body controller **30**, communicate with one another over a controller area bus (CAN) **19**, which in the preferred embodiment conforms to the SAE J1939 protocol. CAN bus **19** provides the necessary means to distribute data on vehicle operating conditions and control vehicle operation to support implementation of the invention. CAN networks allow controllers to place non-addressed data on a bus, in standard formats which identify the character and priority of the data and which still other controllers coupled to the bus can be programmed to recognize and operate on.

**[0038]** The different embodiments of the invention provide alternative means to utilize the available high pressure air, which are implemented using slightly different control arrangements. In a typical application the vehicle will incorporate an air brake system **95** which makes competing demands for compressed air. Requests of brake system **95** for air, which are initiated from the gauge controller **14**, which monitors brake pedal position sensor **81**, are afforded a higher priority than other demands for compressed air. Requests for air and determinations of when to pressurize air are determined only when the vehicle is on, as indicated by the position of an on/off switch **58**, which may be monitored by gauge controller **14** or by body controller **30**. ABS controller **99** may, in some vehicles, be utilized to determine vehicle speed from the wheel rotational speed sensors **97** or from transmission tachometer **170**. Vehicle speed is used for determining when to use compressed air. A transmission controller **130** is provided on vehicles equipped with automatic or semi-automatic transmissions and provides gear selection for the transmission **150** based on engine speed, vehicle speed, available torque and torque demand. Engine controller **20** typically communicates with a tachometer **170** coupled to an output shaft from a transmission **150** to determine vehicle speed.

**[0039]** In the embodiment of **Fig. 4** a hydrostatic motor **160** provides drive train boost on demand. Hydrostatic motor **160** is used to boost a transmission **150** normally driven by the output shaft **152** from engine **16**. Operation of hydrostatic motor **160** is supported by compressed air from a high pressure air tank **77**. Air passes from air tank **70** through a check valve **130** and a valve **85** to hydrostatic motor **170**. Valve **85** is positioned by a solenoid controller in response to a control signal from engine control module **20**. Hydrostatic motor **160** directly boosts transmission **150** to meet part of the torque demand received by the engine controller **20** from body controller **30**, which in turn determines torque demand from the position of an accelerator pedal **54** and torque availability for the engine by subtracting a load estimate from engine capacity (stored in look up tables). Engine controller **20** allocates the response between the hydrostatic motor **160** and engine **16** as a function of engine rpms (determined from cam phase sensor **42**), the availability of compressed air in air tank **70**, provided by a pressure sensor **91**

through body controller **30**, and vehicle speed. Engine **16** has a torque output curve as a function in engine rpm's and load which is low at low rpm's and climbs to a peak as rpm's increase. Supplemental torque is of greatest value for taking off from a standing start where no gear choice is available allowing for operation of the engine in an advantageous portion of the engine torque curve. Boost from hydrostatic motor **160** may also be used to limit loading on output shaft **152** from engine **16** to transmission **150**, allowing the use of a lower weight crankshaft. Vehicles equipped with on board estimation of vehicle load can advantageously adjust the amount of boost to provide the desired acceleration while limiting the load on output shaft **52**. Reducing torque loads on diesel engines also reduces piston blow-by, extending engine oil life and reducing particulate emissions. Exhaust from exhaust manifold **17** is handled conventionally being routed through an exhaust turbine **300** for a turbo-supercharger. Boost is tapered off as engine speed increases and more engine torque becomes available by progressively restricting flow through valve **85**.

**[0040]** Referring to **Fig. 5**, application of the invention in a turbo-compounded engine is illustrated. An exhaust turbine **250** is connected to exhaust manifold **17** and mechanically coupled to output shaft **152** in conventional fashion to boost the output to a transmission **150** from the crankshaft. Compressed air can be fed to the turbine **250** as a substitute for engine exhaust or mixed with the engine exhaust to boost the turbine's mechanical output. Back pressure in power turbine **250** is monitored using a turbine pressure sensor **207** which is connected to engine controller **20** for reporting readings. Providing boost to the output shaft through a power turbine is useful for vehicles for starting the vehicle from a standing start when exhaust back pressure is low. Air release here can be triggered by coincidence of a high torque request from body controller **30**, low speed and by engine load increasing with the vehicle in gear.

**[0041]** Referring to **Fig. 6**, a vehicle is equipped with a turbo-supercharger (comprising turbine **300** and supercharger **261**, which forces air by way of a pressure regulator **262** to an engine intake manifold **108**. Compressed air tank **70** is connected by check valve **130** and valve **85** to feed air to turbine **300** resulting in

increased boost from supercharger **261** by way of pressure regulator **262** to intake manifold **108**. Air pressure in intake manifold **108** is monitored by a pressure sensor **279** which feeds pressure readings to an engine controller **20**. Air is forced into the intake manifold **108** upon occurrence of torque request, low vehicle speed, low engine speed and falling or low intake manifold pressure sensed by pressure sensor **279**. Here, rather than supplying a direct torque boost, the invention promotes good combustion and reduces the intake pumping burden on engine **16** during starts thus providing an indirect boost to torque. Pressure sensor **279** provides feedback limiting for the amount of air released to the intake manifold. While compressed air could in theory be directed directly from the air tank **70** to intake manifold **108** it is considerably simpler from a design perspective to utilize existing supercharger boost arrangements and provide an alternative drive system for the supercharger. Supercharger lag time may also be reduced by using compressed air to spin up the power turbine ahead of exhaust gas availability.

**[0042]** For any of the embodiments, engine **16** load can be estimated by engine controller **20**. Engine control module **20** determines fuel flow for injector controller **48** in response to torque requests from body controller **30**. Engine load is related to brake mean effective pressure which in turn can be estimated as the fuel flow divided by engine speed. Comparison of the result to a look up table keyed to engine rpm's allows determination of the amount of spare capacity available from a diesel.

**[0043]** Referring to **Fig. 7**, a simplified flow chart illustrating operation of the invention is depicted. Vehicle braking has a priority claim on air and accordingly the initial step **700** is a determination if the brake system is engaged. If the brakes are engaged engine **16** may be used to help slow the vehicle and at step **702** engine compression braking is started. Next, at step **704**, tank pressure is read and if it low, step **706** is executed to initiate two stage high pressure air compression. In order to maintain compression braking efficiency, air will be exhausted from the intermediate plenum of the two stage pumps rather than returned to the engine cylinders. If tank pressure does not require adding air, engine pumping may be omitted. Following the



NO branch from step **704**, or following step **706** the process loops to continue monitoring brake position.

**[0044]** If the brakes are determined at step **700** to be disengaged, step **708** is executed to determine if air pressure is too low to permit use of air pressure to permit recovery of energy from the air. It may be noted that the tank pressure limit here may or may not be the same as that measured at step **704**. Making the limit for step **708** lower than the limit for step **704** promotes air compression occurring during periods of braking rather than during any period when spare engine capacity is available. If air tank **70** pressure falls below the minimum required by step **708** the YES branch from the decision block is taken to step **710** where it is determined if the engine has a margin of spare capacity. If YES, split mode operation of engine **16** may be initiated at step **712** to allow some of the cylinders to be used to restore air pressure to a minimum desired level. Following the NO branch from step **710** or step **712** processing loops back through step **700** to determine brake position.

**[0045]** Following the YES branch from step **708** processing is advanced to the torque boost utilization steps using compressed air. It is preferred that use of compressed air for driving a hydrostatic motor or to feed the turbine of a turbo compound engine be implemented with over pressure recovered from vehicle braking and not from running the engine in a split mode under circumstances where engine compression braking is not required. This preference is implemented by limiting operation of the hydrostatic motor and turbo-compounding boost to periods when tank pressure reflects pressure added by engine compression braking. However, for vehicles used as delivery vehicles in urban or suburban areas where there is a great deal of idle time, another loop may be added following the NO branch from step **708** to allow split mode pressure operation during idle periods of the vehicle's engine. This air pressure is available for non-brake devices to reduce variability in engine rpm's. This type of operation can be energy efficient because the engine is allowed to operate at a constant rpm and it should be effective in reducing emissions.

**[0046]** Where the idle option is included, step **714** is executed following a NO decision at step **708** to determine if the transmission is in gear or out of gear. This information is supplied by the transmission controller **130**. If the transmission is out of gear, split mode operation of the engine is permitted to boost tank **70** air pressure to the maximum allowed level. Following the “out of gear” determination, step **725** is executed to determine if tank pressure is at the maximum allowed level. If it is the process returns to the step **700**. If not, split mode operation of the engine to add air is initiated at step **777** and processing returns to brake position determination step **700**.

**[0047]** Following determination that the transmission is reported to be in gear at step **714**, step **716** is executed to determine if engine rpm's are falling. If YES, then step **720** is executed to determine if torque is being requested by the body controller **30**. If this determination is also affirmative, then air is released to boost torque output at step **722**. Following step **722** or the NO branch of step **720** process execution is returned to brake position determination at step **700**. Following the NO branch from step **716**, step **718** is executed to determine if vehicle speed is low, or stopped. If YES, step **720** follows. If NO, processing returns to the brake position determination step **700**. It will be understood that the steps **716** and **718** could be rearranged, or that a step determining whether intake manifold pressure was low could be substituted if measuring for declining engine rpm's.

**[0048]** Allocation of the load between the internal combustion engine and the pressurized air output boost system is determined by the engine controller **20** which varies the position of valve **85** to control flow of compressed air. Available torque from compressed air is readily determined empirically and stored in look up tables.

**[0049]** The invention provides for recapturing and reusing kinetic energy otherwise lost during braking by employing temporarily unused or unneeded cylinders in a diesel engine as first stages in high pressure two stage air pumps. The energy is recycled in a number of ways to boost drive train output, such as deploying compressed air supply torque to the transmission using a hydrostatic

motor, delivering the air to the turbine of an turbo-compound engine, or increasing intake manifold pressure by driving the power turbine for a turbo-supercharger. The consequential reduction in load on the engine during take off from a standing start or during periods climbing an upgrade which require low engine speed operation can reduce pollutant production otherwise characteristic of diesels at low rpms.

**[0050]** While the invention is shown in only one of its forms, it is not thus limited but is susceptible to various changes and modifications without departing from the spirit and scope of the invention.